

Curtis Primo Cappuccino NEXT GENERATION - PCNG



Curtis Primo Cappuccino



Primo Cappuccino Dispenser – Up to 6 dispensing stations with pre-dispense or portion control.

G3 Digital Control Module – Provides precise control over all critical blending and dispensing functions.

Pre-Dispense – Easy To Use. Choose a size from small, medium or large by the touch of a button.

Irradiant LCD Digital Display – Extra bright and easy to see.

Scroll-Through Precision Programming – Adjust powder flow in 5% increments and water temperature from 80°F to 200°F to create the perfect hot or cold beverage for your operation.

Direct Drive Mixing Augers – Ensure smooth high-speed blending of powdered drinks.

High Velocity Whipping Motors – Sloped whipping motors ensure smooth, high-speed blending of powdered drinks.

Fixed-Flow Water System – Ensures precise drink blending regardless of irregularities in water pressure/volume.

Curtis Primo Cappuccino. Rich in Design. Rich in Features. Rich in Profits.

The first thing you'll notice about the Primo Cappuccino is its smooth Euro-Styled lines and cup locator guides. Built right into the oversized alcove, the guides ensure proper alignment with the dispensing nozzle while the increased cup clearance accommodates the most popular cup sizes. The PCNG captures attention from the moment your customers walk in... stimulating more impulse sales.

Curtis has incorporated the industry's most advanced digital technology – G3 – into the Primo Cappuccino Machine. It's this G3 technology that dramatically simplifies use, minimizes maintenance costs and increases profitability.



PCNG - Specifications

Model No.	Description	Dimensions	Ship Weight	Ship Cube
PCNG 3	3 Dispensing Points (One 5 lb and Two 10 lb Hoppers)	36.24 x 14.64 x 23.08		
PCNG 4	4 Dispensing Points (Two 5 lb and Two 10 lb Hoppers)	36.24 x 21.23 x 23.08		
PCNG 5	5 Dispensing Points (Three 5 lb and Two 10 lb Hoppers)	36.24 x 21.23 x 23.08		
PCNG 6	6 Dispensing Points (Two 3 lb, Three 5 lb and One 10 lb Hopper)	36.24 x 21.23 x 23.08		

Electrical Supply Requirements

Voltage	Wattage	Amperage	Wire	Hertz	Phase	Heat Config.	Min. Circuit Req.
120V	1800W	15A	2W + G	50/60 Hz	Single Phase	2X1600W	15/20A

Water Supply Requirements

Brewer Capacity

Min. Flow Rate	Water Connector	Water Pressure	1650W	2800W	Water Tank Volume
1 GPM	1/4" Flare	20-90 psi	4.5 gal/hr	10.0 gal/hr	5.3 gal



WARNING - These products can expose you to chemicals including Acrylamide and Bisphenol A (BPA), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information visit www.P65Warnings.ca.gov



PERFECTING THE ART OF BREWING SINCE 1941

wilburcurtis.com